

DATASHEET - CPA50A

rev A

C-band GaN Power Amplifier		min	typ	max	unit	note
1.0	General	The CPA50A is a C-band GaN Power Amplifier module designed for 6cm Ham Radio communication systems. The unit includes an built-in output isolator to protect the output stage against excessive mismatch.				
1.1	RF frequency		5.76		GHz	
1.2	Linear Gain		40		dB	
1.3.1	RF output power, Psat @ Vdd = 28V	50			W	
1.3.2		47			dBm	
1.4	In- and Output- impedance		50		Ohm	
1.5	Input return loss		13		dB	
1.6.	Output return loss		17		dB	
1.7.1	Input drive level	at Psat		10		dBm
1.7.2		no damage		14		dBm
1.8	Supply voltage, Vdd	24	28	30	V	
1.9.1	Supply current, Idd @ Pout = 50W	no RF		0.25		A
1.9.2				3.7		A
1.10	Electrical stability	unconditional			with matched ports	
1.11	Input connector	SMA/f				
1.12	Output connector	SMA/f				
1.13	DC connection	soldered to feedthrough cap				
1.14	Dimensions	146 x 38 x 20		mm	overall	
1.15	Weight		220		g	
1.16	Heatsink requirement			0.2	K/W	use heatsink compound
1.17	Mounting holes	4 x M3			in 125 x 34 mm pattern	
1.18	Operational temperature range	-25		+55	°C	
1.19	Humidity protection	none				